

# SureSignal®

Temperature transmitters for industrial use

**4 Year Warranty**



PACKAGING	INPUTS	OUTPUTS	POWER
3.2"x 2.3" Encapsulated	Thermistor	4 to 20 mA	Battery
3.2"x 2.6" Encapsulated	RTD	0 to 20 mA	120 VAC
3.5" Square Encapsulated	Thermocouple	1 to 20 mA	208 VAC
4.5"x 3.0" Encapsulated	Logic VDC	Any mA Range	240 VAC
Custom Encapsulated	Logic VAC	0 to 1 VDC	480 VAC
Custom Open PC Board	Logic Current	0 to 2.5 VDC	24 & 48 VAC
Vast Library of PC Boards	Analog VDC	0 to 5 VDC	3.3 to 48 VAC
Wall Mount Enclosure	Analog Current	0 to 10 VDC	Power Over Ethernet
Custom Enclosure	Frequency	Any VDC Range	85 to 265 VAC Universal

TERMINATIONS	INTERFACE
Fast-Ons	Protocol Matching
Terminal Blocks	RS 232
Euro Style Connectors	RS 485
Plug-in Connectors	RS 422
Locking Connectors	USB
Military Connectors	I <sup>2</sup> C
Pigtail Wire Leads	CANbus
Custom Harnesses	Ethernet
D SUB Connectors	GPIB
Right Angle Connectors	Modbus

